

A CHARACTERIZATION OF COUPLE-STRESS FLUID HEATED FROM BELOW IN A POROUS MEDIUM IN THE PRESENCE OF A ROTATION

Ajaib S. Banyal¹ and Kamal Singh²

¹Department of Mathematics, Govt. College Nadaun, Dist. Hamirpur, (HP) INDIA 177033

²Department of Mathematics, Govt. College Dehri, Dist. Kangra, (HP) INDIA 176022

¹Corresponding Author E mail: ajaihbanyal@rediffmail.com, Fax No. : 01972232688

[Received-19/05/2011, Accepted-30/07/2012]

ABSTRACT

The thermal instability of a couple-stress fluid heated from below in a porous medium acted upon by uniform vertical rotation is investigated. Following the linearized stability theory and normal mode analysis, the paper mathematically established the conditions for characterizing the oscillatory motions which may be neutral or unstable for rigid boundaries at the top and bottom of the fluid. It is established that all non-decaying slow motions starting from rest, in a couple-stress fluid of infinite horizontal extension and finite vertical depth, which is acted upon by uniform vertical rotation and a constant vertical adverse temperature gradient, are necessarily non-oscillatory, in the regime

$$T_A \leq \frac{\pi^4 F^2}{P_l^2},$$

where T_A is the Taylor number, P_l is the dimensionless medium permeability of the porous medium and F is the couple-stress parameter. The result is important since the exact solutions of the problem investigated are not obtainable in closed form, when both the boundaries are rigid.

Key Words: Thermal convection; Couple-Stress Fluid; Rotation; PES; Taylor number.

MSC 2000 No.: 76A05, 76E06, 76E15; 76E07.

1. INTRODUCTION

Stability of a dynamical system is closest to real life, in the sense that realization of a dynamical system depends upon its stability. Right from the conceptualizations of turbulence, instability of fluid flows is being regarded at its root. A detailed account of the theoretical and experimental study

of the onset of thermal instability in Newtonian fluids, under varying assumptions of hydrodynamics and hydromagnetics, has been given by Chandrasekhar [1] and the Boussinesq approximation has been used throughout, which states that the density changes are disregarded in all other terms in the equation of motion, except in

the external force term. The formation and derivation of the basic equations of a layer of fluid heated from below in a porous medium, using the Boussinesq approximation, has been given in a treatise by Joseph [2]. When a fluid permeates through an isotropic and homogeneous porous medium, the gross effect is represented by Darcy's law. The study of layer of fluid heated from below in porous media is motivated both theoretically and by its practical applications in engineering. Among the applications in engineering disciplines one can name the food processing industry, the chemical processing industry, solidification, and the centrifugal casting of metals. The development of geothermal power resources has increased general interest in the properties of convection in a porous medium. Stommel and Fedorov [3] and Linden [4] have remarked that the length scales characteristic of double-diffusive convecting layers in the ocean may be sufficiently large so that the Earth's rotation might be important in their formation. Moreover, the rotation of the Earth distorts the boundaries of a hexagonal convection cell in a fluid through porous medium, and this distortion plays an important role in the extraction of energy in geothermal regions. The forced convection in a fluid saturated porous medium channel has been studied by Nield et al [5]. An extensive and updated account of convection in porous media has been given by Nield and Bejan [6].

The effect of a magnetic field on the stability of such a flow is of interest in geophysics, particularly in the study of the earth's core, where the earth's mantle, which consist of conducting fluid, behaves like a porous medium that can become conductively unstable as result of differential diffusion. Another application of the results of flow through a porous medium in the presence of magnetic field is in the study of the stability of convective geothermal flow. A good account of the effect of rotation and magnetic field

on the layer of fluid heated from below has been given in a treatise by Chandrasekhar [1].

MHD finds vital applications in MHD generators, MHD flow-meters and pumps for pumping liquid metals in metallurgy, geophysics, MHD couplers and bearings, and physiological processes such magnetic therapy. With the growing importance of non-Newtonian fluids in modern technology and industries, investigations of such fluids are desirable. The presence of small amounts of additives in a lubricant can improve bearing performance by increasing the lubricant viscosity and thus producing an increase in the load capacity. These additives in a lubricant also reduce the coefficient of friction and increase the temperature range in which the bearing can operate.

Darcy's law governs the flow of a Newtonian fluid through an isotropic and homogeneous porous medium. However, to be mathematically compatible and physically consistent with the Navier-Stokes equations, Brinkman [7] heuristically proposed the introduction of the term

$\frac{\mu}{\epsilon} \nabla^2 \vec{q}$, (now known as Brinkman term) in

addition to the Darcian term $-\left(\frac{\mu}{k_1}\right) \vec{q}$. But the

main effect is through the Darcian term; Brinkman term contributes very little effect for flow through a porous medium. Therefore, Darcy's law is proposed heuristically to govern the flow of this non-Newtonian couple-stress fluid through porous medium. A number of theories of the micro continuum have been postulated and applied (Stokes [8]; Lai et al [9]; Walicka [10]). The theory due to Stokes [8] allows for polar effects such as the presence of couple stresses and body couples. Stokes's [8] theory has been applied to the study of some simple lubrication problems (see e.g. Sinha et al [11]; Bujurke and Jayaraman [12]; Lin [13]). According to the theory of Stokes [8],

couple-stresses are found to appear in noticeable magnitudes in fluids with very large molecules. Since the long chain hyaluronic acid molecules are found as additives in synovial fluid, Walicki and Walicka [14] modeled synovial fluid as couple stress fluid in human joints. The study is motivated by a model of synovial fluid. The synovial fluid is natural lubricant of joints of the vertebrates. The detailed description of the joints lubrication has very important practical implications; practically all diseases of joints are caused by or connected with a malfunction of the lubrication. The external efficiency of the physiological joint lubrication is caused by more mechanisms. The synovial fluid is caused by the content of the hyaluronic acid, a fluid of high viscosity, near to a gel. A layer of such fluid heated from below in a porous medium under the action of magnetic field and rotation may find applications in physiological processes. MHD finds applications in physiological processes such as magnetic therapy; rotation and heating may find applications in physiotherapy. The use of magnetic field is being made for the clinical purposes in detection and cure of certain diseases with the help of magnetic field devices.

Sharma and Thakur [15] have studied the thermal convection in couple-stress fluid in porous medium in hydromagnetics. Sharma and Sharma [16] have studied the couple-stress fluid heated from below in porous medium. Kumar and Kumar [17] have studied the combined effect of dust particles, magnetic field and rotation on couple-stress fluid heated from below and for the case of stationary convection, found that dust particles have destabilizing effect on the system, where as the rotation is found to have stabilizing effect on the system, however couple-stress and magnetic field are found to have both stabilizing and destabilizing effects under certain conditions. Sunil et al. [18] have studied the global stability for thermal convection in a couple-stress fluid heated from below and found couple-stress fluids

are thermally more stable than the ordinary viscous fluids.

Pellow and Southwell [19] proved the validity of PES for the classical Rayleigh-Bénard convection problem. Banerjee et al [20] gave a new scheme for combining the governing equations of thermohaline convection, which is shown to lead to the bounds for the complex growth rate of the arbitrary oscillatory perturbations, neutral or unstable for all combinations of dynamically rigid or free boundaries and, Banerjee and Banerjee [21] established a criterion on characterization of non-oscillatory motions in hydrodynamics which was further extended by Gupta et al. [22]. However no such result existed for non-Newtonian fluid configurations, in general and for couple-stress fluid configurations, in particular. Banyal [23] have characterized the non-oscillatory motions in couple-stress fluid.

Keeping in mind the importance of non-Newtonian fluids, as stated above, this article attempts to characterize the oscillatory motions in the couple-stress fluid heated from below in a porous medium in the presence of uniform rotation with realistic rigid-rigid horizontal boundaries and it has been established that the onset of instability in a couple-stress fluid in a porous medium heated from below, in the presence of uniform vertical rotation, cannot manifest itself as oscillatory motions of growing amplitude if the thermal Taylor number T_A , the couple-stress parameter of the fluid F and the medium permeability P_l ,

satisfy the inequality $T_A \leq \frac{\pi^4 F^2}{P_l^2}$, when the

bounding surfaces are rigid of infinite horizontal extension.

2. FORMULATION OF THE PROBLEM AND PERTURBATION EQUATIONS

Here we consider an infinite, horizontal, incompressible couple-stress fluid layer, of thickness d , heated from below so that, the

temperature and density at the bottom surface $z = 0$ are T_0 and ρ_0 and at the upper surface $z = d$ are T_d and ρ_d respectively, and that a uniform adverse temperature gradient $\beta \left(= \left| \frac{dT}{dz} \right| \right)$ is maintained. The fluid is acted upon by a uniform vertical rotation $\vec{\Omega}(0,0,\Omega)$. This fluid layer is flowing through an isotropic and homogeneous porous medium of porosity \mathcal{E} and of medium permeability k_1 .

Let ρ , p , T , and $\vec{q}(u, v, w)$ denote respectively the fluid density, pressure, temperature and filter velocity of the fluid, respectively. Then the momentum balance, mass balance, and energy balance equation of couple-stress fluid through porous medium, governing the flow of couple-stress fluid in the presence of uniform vertical rotation are (Stokes [8]; Joseph [2]; Chandrasekhar [1]) are given by

$$\frac{1}{\mathcal{E}} \left[\frac{\partial \vec{q}}{\partial t} + \frac{1}{\mathcal{E}} (\vec{q} \cdot \nabla) \vec{q} \right] = -\nabla \left(\frac{p}{\rho_0} - \frac{1}{2} |\vec{\Omega} \times \vec{r}|^2 \right) + g \left(1 + \frac{\delta \rho}{\rho_0} \right) - \frac{1}{k_1} \left(\nu - \frac{\mu'}{\rho_0} \nabla^2 \right) \vec{q} + \frac{2}{\mathcal{E}} (\vec{q} \times \vec{\Omega}), \quad (1)$$

$$\nabla \cdot \vec{q} = 0, \quad (2)$$

$$E \frac{dT}{dt} + (\vec{q} \cdot \nabla) T = \kappa \nabla^2 T, \quad (3)$$

Where $\frac{d}{dt} = \frac{\partial}{\partial t} + \mathcal{E}^{-1} \vec{q} \cdot \nabla$, stands for the convective derivatives. Here

$$E = \mathcal{E} + (1 - \mathcal{E}) \left(\frac{\rho_s c_s}{\rho_0 c_v} \right),$$

is a constant, while ρ_s , c_s and ρ_0 , c_v , stands for the density and heat

capacity of the solid (porous matrix) material and the fluid, respectively, \mathcal{E} is the medium porosity and $r(x, y, z)$.

The equation of state is

$$\rho = \rho_0 [1 - \alpha(T - T_0)], \quad (4)$$

Where the suffix zero refer to the values at the reference level $z = 0$. Here $\vec{g}(0,0,-g)$ is acceleration due to gravity and α is the coefficient of thermal expansion. In writing the equation (1), we made use of the Boussinesq approximation, which states that the density variations are ignored in all terms in the equation of

motion except the external force term. The kinematic viscosity ν , couple-stress viscosity μ' , thermal diffusivity κ and the coefficient of thermal expansion α are all assumed to be constants.

The basic motionless solution is

$$\vec{q} = (0,0,0), \quad \rho = \rho_0(1 + \alpha\beta z), \quad p = p(z), \quad T = -\beta z + T_0, \quad (5)$$

Here we use the linearized stability theory and the normal mode analysis method. Assume small perturbations around the basic solution, and let $\delta\rho$, δp , θ and $\vec{q}(u, v, w)$ denote respectively the perturbations in density ρ , pressure p , temperature T and velocity $\vec{q}(0,0,0)$ respectively. The change in density $\delta\rho$, caused mainly by the perturbation θ in temperature, is given by

$$\rho + \delta\rho = \rho_0[1 - \alpha(T + \theta - T_0)] = \rho - \alpha\rho_0\theta, \text{ i.e. } \delta\rho = -\alpha\rho_0\theta. \quad (6)$$

Then the linearized perturbation equations of the couple-stress fluid reduces to

$$\frac{1}{\varepsilon} \frac{\partial \vec{q}}{\partial t} = -\frac{1}{\rho_0} \nabla \delta p - \vec{g} \alpha \theta - \frac{1}{k_1} \left(\nu - \frac{\mu'}{\rho_0} \nabla^2 \right) \vec{q} + \frac{2}{\varepsilon} \left(\vec{q} \times \vec{\Omega} \right), \quad (7)$$

$$\nabla \cdot \vec{q} = 0, \quad (8)$$

$$E \frac{\partial \theta}{\partial t} = \beta w + \kappa \nabla^2 \theta, \quad (9)$$

3. Normal Mode Analysis

Analyzing the disturbances into two-dimensional waves, and considering disturbances characterized by a particular wave number, we assume that the Perturbation quantities are of the form

$$[w, \theta, \zeta] = [W(z), \Theta(z), Z(z)] \exp(ik_x x + ik_y y + nt), \quad (10)$$

Where k_x, k_y are the wave numbers along the x- and y-directions, respectively, $k = (k_x^2 + k_y^2)^{\frac{1}{2}}$, is the resultant wave number, n is the growth rate which is, in general, a complex constant and,

$\zeta = \frac{\partial v}{\partial x} - \frac{\partial u}{\partial y}$ denote the z-component of vorticity; $W(z), \Theta(z)$ and $Z(z)$ are the functions of z only.

Using (10), equations (7)-(9), within the framework of Boussinesq approximations, in the non-dimensional form transform to

$$(D^2 - a^2) \left[\left(\frac{\sigma}{\varepsilon} + \frac{1}{P_l} \right) - \frac{F}{P_l} (D^2 - a^2) \right] W = -Ra^2 \Theta - T_A DZ, \quad (11)$$

$$\left[\frac{F}{P_l} (D^2 - a^2) - \left(\frac{\sigma}{\varepsilon} + \frac{1}{P_l} \right) \right] Z = -DW, \quad (12)$$

and

$$(D^2 - a^2 - Ep_1 \sigma) \Theta = -W, \quad (13)$$

Where we have introduced new coordinates $(x', y', z') = (x/d, y/d, z/d)$ in new units of length and $D = d / dz'$. For convenience, the dashes are dropped hereafter. Also we have substituted

$$a = kd, \sigma = \frac{nd^2}{\nu}, p_1 = \frac{\nu}{\kappa}, \text{ is the thermal Prandtl number; } P_l = \frac{k_1}{d^2} \text{ is the dimensionless}$$

medium permeability, $F = \frac{\mu' / (\rho_0 d^2)}{\nu}$, is the dimensionless couple-stress viscosity parameter;

$$R = \frac{g \alpha \beta d^4}{\kappa \nu}, \text{ is the thermal Rayleigh number; and } T_A = \frac{4 \Omega^2 d^4}{\nu^2 \varepsilon^2}, \text{ is the Taylor number. Also we}$$

have substituted $W = W_{\oplus}$, $\Theta = \frac{\beta d^2}{\kappa} \Theta_{\oplus}$, $Z = \frac{2 \Omega d}{\nu \varepsilon} Z_{\oplus}$, and $D_{\oplus} = dD$, and dropped (\oplus) for convenience.

We now consider the case where both the boundaries are rigid and are maintained at constant temperature, and then the perturbations in the temperature are zero at the boundaries. The appropriate boundary conditions with respect to which equations (11)-(13), must possess a solution are

$$W = DW = 0, \Theta = 0 \text{ and } Z=0 \text{ at } z = 0 \text{ and } z = 1. \quad (14)$$

Equations (11)-(13), along with boundary conditions (14), pose an eigenvalue problem for σ and we wish to characterize σ_i , when $\sigma_r \geq 0$.

4. Mathematical Analysis

We prove the following theorem:

Theorem: If $R > 0$, $F > 0$, $T_A > 0$, $\sigma_r \geq 0$ and $\sigma_i \neq 0$ then the necessary condition for the existence of non-trivial solution (W, Θ, Z) of equations (16), (17) and (18) together with boundary conditions (19) is that

$$T_A \rangle \frac{\pi^4 F^2}{P_l^2} .$$

Proof: Multiplying equation (11) by W^* (the complex conjugate of W) throughout and integrating the resulting equation over the vertical range of z , we get

$$\left(\frac{\sigma}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 W^* (D^2 - a^2) W dz - \frac{F}{P_l} \int_0^1 W^* (D^2 - a^2)^2 W dz = -Ra^2 \int_0^1 W^* \Theta dz - T_A \int_0^1 W^* DZ dz, \quad (15)$$

Taking complex conjugate on both sides of equation (13), we get

$$(D^2 - a^2 - Ep_1 \sigma^*) \Theta^* = -W^*, \quad (16)$$

Therefore, using (16), we get

$$\int_0^1 W^* \Theta dz = - \int_0^1 \Theta (D^2 - a^2 - Ep_1 \sigma^*) \Theta^* dz, \quad (17)$$

Also taking complex conjugate on both sides of equation (12), we get

$$\frac{F}{P_l} (D^2 - a^2) Z^* - \left(\frac{\sigma^*}{\varepsilon} + \frac{1}{P_l}\right) Z^* = -DW^*, \quad (18)$$

Therefore, using (18), we get

$$\int_0^1 W^* DZ dz = - \int_0^1 DW^* Z dz = \frac{F}{P_l} \int_0^1 Z^* (D^2 - a^2) Z dz - \left(\frac{\sigma^*}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 Z^* Z dz, \quad (19)$$

Substituting (17) and (19) in the right hand side of equation (15), we get

$$\begin{aligned} & \left(\frac{\sigma}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 W^* (D^2 - a^2) W dz - \frac{F}{P_l} \int_0^1 W^* (D^2 - a^2)^2 W dz \\ &= Ra^2 \int_0^1 \Theta (D^2 - a^2 - Ep_1 \sigma^*) \Theta^* dz - \frac{T_A F}{P_l} \int_0^1 Z (D^2 - a^2) Z^* dz + T_A \left(\frac{\sigma^*}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 Z^* Z dz, \end{aligned} \quad (20)$$

Integrating the terms on both sides of equation (25) for an appropriate number of times by making use of the appropriate boundary conditions (19), along with (17), we get

$$\begin{aligned} & \left(\frac{\sigma}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 \{ |DW|^2 + a^2 |W|^2 \} dz + \frac{F}{P_l} \int_0^1 \{ |D^2 W|^2 + 2a^2 |DW|^2 + a^4 |W|^2 \} dz \\ &= Ra^2 \int_0^1 \{ |D\Theta|^2 + a^2 |\Theta|^2 + Ep_1 \sigma^* |\Theta|^2 \} dz - \frac{T_A F}{P_l} \int_0^1 \{ |DZ|^2 + a^2 |Z|^2 \} dz - T_A \left(\frac{\sigma^*}{\varepsilon} + \frac{1}{P_l}\right) \int_0^1 |Z|^2 dz, \end{aligned} \quad (21)$$

now equating imaginary parts on both sides of equation (21), and cancelling $\sigma_i (\neq 0)$ throughout from imaginary part, we get

$$\frac{1}{\varepsilon} \int_0^1 \{ |DW|^2 + a^2 |W|^2 \} dz = -Ra^2 Ep_1 \int_0^1 |\Theta|^2 dz + \frac{T_A}{\varepsilon} \int_0^1 |Z|^2 dz, \tag{22}$$

We first note that since W and Z satisfy $W(0) = 0 = W(1)$ and $Z(0) = 0 = Z(1)$ in addition to satisfying to governing equations and hence we have from the Rayleigh-Ritz inequality; Schultz [24],

$$\int_0^1 |DW|^2 dz \geq \pi^2 \int_0^1 |W|^2 dz, \tag{23}$$

and

$$\int_0^1 |DZ|^2 dz \geq \pi^2 \int_0^1 |Z|^2 dz, \tag{24}$$

Further, for $W(0) = 0 = W(1)$ and $Z(0) = 0 = Z(1)$, Banerjee et al. [25] have show that

$$\int_0^1 |D^2W|^2 dz \geq \pi^2 \int_0^1 |DW|^2 dz \text{ and } \int_0^1 |D^2Z|^2 dz \geq \pi^2 \int_0^1 |DZ|^2 dz, \tag{25}$$

Further, multiplying equation (12) and its complex conjugate (18), and integrating by parts each term on both sides of the resulting equation for an appropriate number of times and making use of boundary condition on Z namely $Z(0) = 0 = Z(1)$, we get

$$\begin{aligned} & \frac{F^2}{P_l^2} \int_0^1 \{ |D^2Z|^2 + 2a^2 |DZ|^2 + a^4 |Z|^2 \} dz + \frac{2F}{P_l} \left(\frac{\sigma_r}{\varepsilon} + \frac{1}{P_l} \right) \int_0^1 \{ |DZ|^2 + a^2 |Z|^2 \} dz \\ & + \left\{ \frac{|\sigma|^2}{\varepsilon^2} + \frac{2\sigma_r}{\varepsilon P_l} + \frac{1}{P_l^2} \right\} \int_0^1 |Z|^2 dz = \int_0^1 |DW|^2 dz, \end{aligned} \tag{26}$$

Now $F > 0, P_l > 0, \varepsilon > 0$ and $\sigma_r \geq 0$, therefore the equation (26) gives,

$$\frac{F^2}{P_l^2} \int_0^1 |D^2Z|^2 dz < \int_0^1 |DW|^2 dz, \tag{27}$$

And on utilizing the inequalities (24) and (25), inequality (27) gives

$$\int_0^1 |Z|^2 dz < \frac{P_l^2}{\pi^4 F^2} \int_0^1 |DW|^2 dz, \tag{28}$$

Now $R > 0, \varepsilon > 0$ and $T_A > 0$, utilizing the inequalities (28), the equation (22) gives,

$$\frac{1}{\epsilon} \left[1 - \frac{P_l^2 T_A}{(\pi^4 F^2)} \right] \int_0^1 |DW|^2 dz + \frac{a^2}{\epsilon} \int_0^1 |W|^2 dz + Ra^2 Ep_1 \int_0^1 |\Theta|^2 dz < 0, \quad (29)$$

and therefore , we must have

$$T_A > \frac{\pi^4 F^2}{P_l^2}. \quad (30)$$

Hence, if

$$\sigma_r \geq 0 \text{ and } \sigma_i \neq 0, \text{ then } T_A > \frac{\pi^4 F^2}{P_l^2} .$$

And this completes the proof of the theorem. Presented otherwise from the point of view of existence of instability as stationary convection, the above theorem can be put in the form as follow:-

Theorem 2: The sufficient condition for the validity of the ‘exchange principle’ and the onset of instability as a non-oscillatory motions of non-growing amplitude in a couple-stress fluid in a porous medium heated from below, in the presence of uniform vertical rotation is that,

$$T_A \leq \frac{\pi^4 F^2}{P_l^2}, \text{ where } T_A \text{ is the Taylor number,}$$

P_l is the medium permeability and F is the couple-stress parameter, when the boundaries are rigid.

or

The onset of instability in a couple-stress fluid in a porous medium heated from below, in the presence of uniform vertical rotation, cannot manifest itself as oscillatory motions of growing amplitude if the Taylor number T_A , the medium permeability P_l and the couple-stress parameter F ,

satisfy the inequality $T_A \leq \frac{\pi^4 F^2}{P_l^2}$, when both the

bounding surfaces are rigid.

In the context of existence of instability in ‘oscillatory modes’ and that of ‘overstability’ in the present configuration, we can state the above theorem as follow:-

Theorem 3: The necessary condition for the existence of instability in ‘oscillatory modes’ and that of ‘overstability’ in a couple-stress fluid in a porous medium heated from below, in the presence of uniform vertical rotation is that the Taylor number T_A , the couple-stress parameter of the fluid F and the medium permeability P_l , must

satisfy the inequality $T_A > \frac{\pi^4 F^2}{P_l^2}$, when both the

bounding surfaces are rigid

5. CONCLUSIONS

This theorem mathematically established that the onset of instability in a couple-stress fluid in the presence of uniform vertical rotation, cannot

manifest itself as oscillatory motions of growing amplitude if the Taylor number T_A , the couple-stress parameter of the fluid F and the medium permeability P_l , satisfy the inequality $T_A \leq \frac{\pi^4 F^2}{P_l^2}$, when both the bounding surfaces are rigid.

The essential content of the theorem, from the point of view of linear stability theory is that for the configuration of couple-stress fluid of infinite horizontal extension heated from below, having rigid boundaries at the top and bottom of the fluid, in the presence of uniform vertical rotation, parallel to the force field of gravity, an arbitrary neutral or unstable modes of the system are definitely non-oscillatory in character if $T_A \leq \frac{\pi^4 F^2}{P_l^2}$, and in particular PES is valid.

6. REFERENCES

1. Chandrasekhar, S., Hydrodynamic and Hydromagnetic Stability, Dover Publications, New York, 1981.
2. Joseph, D.D., Stability of fluid motions, vol.II, Springer-Verlag, Berlin, 1976.
3. Stommel, H., and Fedorov, K.N., Small scale structure in temperature and salinity near Timor and Mindano, Tellus 1967, vol. 19, pp. 306-325
4. Linden, P.F., Salt fingers in a steady shear flow, Geophys. Fluid Dynamics, 1974, vol.6, pp.1-27.
5. Nield, D.A., and Junqueira, S.L.M. and Lage, J.L., Forced convection in a fluid saturated porous medium a channel with isothermal or isoflux boundaries, J. fluid Mech. 1996, vol.322, pp. 201-214.
6. Nield, D.A., and Bejan, A., Convection in porous medium, Springer and Verlag, Newyark, 1999.
7. Brinkman, H.C., problems of fluid flow through swarms of particles and through macromolecules in solution, research(London) 1949, Vol. 2, p.190.
8. Stokes, V.K., Couple-stress in fluids, Phys. Fluids, 1966, Vol. 9, pp.1709-15.
9. Lai, W.M., Kuei, S.C., and Mow, V.C., Rheological equations for synovial fluids, J. of Biomechanical eng. 1978, vol.100, pp. 169-186.
10. Walicka, A., Micropolar flow in a slot between rotating surfaces of revolution, Zielona Gora, TU Press, 1994.
11. Sinha, P., Singh, C., and Prasad, K.R., Couple-stresses in journal bearing lubricants and the effect of convection, Wear, vol.67, pp. 15-24, 1981.
12. Bujurke, N.M., and Jayaraman, G., The influence of couple-stresses in squeeze films Int. J. Mech. Sci. 1982, Vol. 24, pp.369-376.
13. Lin, J.R., Couple-stress effect on the squeeze film characteristics of hemispherical bearing with reference to synovial joints, Appl. Mech. engg. 1996, vol. 1, pp.317-332.
14. Walicki, E. and Walicka, A., Inertial effect in the squeeze film of couple-stress fluids in biological bearings, Int. J. Appl. Mech. Engg. 1999, Vol. 4, pp. 363-373.
15. Sharma, R.C. and Thakur, K. D., Couple stress-fluids heated from below in hydromagnetics, Czech. J. Phys. 2000, Vol. 50, pp. 753-58.
16. Sharma, R.C. and Sharma S., On couple-stress fluid heated from below in porous medium, Indian J. Phys 2001, Vol. 75B, pp.59-61.
17. Kumar, V. and Kumar, S., On a couple-stress fluid heated from below in hydromagnetics, Appl. Appl. Math. 2011, Vol. 05(10), pp. 1529-1542.
18. Sunil, Devi, R. and Mahajan, A., Global stability for thermal convection in a couple stress-fluid, Int. comm.. Heat and Mass Transfer 2011, 38, pp. 938-942.
19. Pellow, A., and Southwell, R.V., On the maintained convective motion in a fluid heated from below. Proc. Roy. Soc. London A, 1940, 176, 312-43.
20. Banerjee, M.B., Katoch, D.C., Dube, G.S. and Banerjee, K., Bounds for growth rate of perturbation in thermohaline convection. Proc. R. Soc. A, 1981, 378, 301-04.
21. Banerjee, M. B., and Banerjee, B., A characterization of non-oscillatory motions in

- magneto-hydraulics. *Ind. J. Pure & Appl Maths.*, 1984, 15(4): 377-382.
22. Gupta, J.R., Sood, S.K., and Bhardwaj, U.D., On the characterization of nonoscillatory motions in rotatory hydromagnetic thermohaline convection, *Indian J. pure appl.Math.* 1986,17(1) pp 100-107.
 23. Banyal, A.S, The necessary condition for the onset of stationary convection in couple-stress fluid, *Int. J. of Fluid Mech. Research*, Vol. 38, No.5, 2011, pp. 450-457.
 24. Schultz, M.H., *Spline Analysis*, Prentice Hall, Englewood Cliffs, New Jersey, 1973.
 25. Banerjee, M.B., Gupta, J.R. and Prakash, J. On thermohaline convection of Veronis type, *J. Math. Anal. Appl.*, Vol.179, No. 2, 1992, pp. 327-334.